

WALL MOUNTED VENTILATION FAN

Featuring the first ever Dual Airflow Wall Mounted Ventilation Fan in Malaysia; best suited for kitchens, washrooms, and even altar rooms for optimum air dilution. Improving indoor air ventilation is vital in our homes today to battle Covid-19 and other airborne diseases by keeping virus particles from accumulating indoors. It also has a high-quality, reputable NSK/NMB ball bearing fitted for 10 times the lifespan of a typical oil bearing.

FEATURES



HIGH PERFORMANCE COPPER WINDING



STRONG ANTI



SHORT-CIRCUI

	Air Flow (CFM)	180	450
IT	Noise Level (dB)	40	45
	Mounting Hole Size	193 x 193	290 x 290

MODEL




DUAL AIRFLOW OPERATION



ENERGY SAVING

NSK / NMB HIGH QUALITY BALL BEARING



MODEL	DE-180	DE-450
Α	160	270
В	254	343
С	210	323
D	225	343
E	190 x 190	290 x 290
F	77	75
G	30	30
Н	45	65

DE-180

DE-450 450

Measurements in millimeters



DUAL AIRFLOW VENTILATION FAN HIGHLIGHTS



EXHAUST OUTWARD

On default operation, the fan will exhaust outward, drawing air outside, and clear ing bad odors and humidity.



REVERSIBLE FLOW

The fan runs in reverse and blows inwards, promoting the circulation of fresh air.