

C8 CIRCULATOR SERIES

HÖUM® C8 comes with powerful aerodynamic turbo design for maximum airflow. A bigger brother to the C6 with shared modern aesthetics, featuring adjustable knobs for easy and fast control in any space.



*C8 DC AIR CIRCULATOR FAN

SPECIFICATION

Model	C8	C8 DC
Motor Type	AC	DC
Rated Voltage	220-240 V~	220-240 V~
Rated Frequency	50 Hz	50 Hz
Rated Power	50 W	26 W
Noise (Max.)	≤55 dB	≤56 dB
Air Volume	Speed 5, 18 m³/min	Speed 32, 20m³/min
Unit Weight	3.1 KG	2.5 KG
Dimensions (W x H x D)	250 x 355 x 255 mm	255 x 374 x 237 mm
Air Distance (Max.)	20 meter	20 meter
Air Velocity	Speed 5, 6.5 m/s Speed 4, 5.5 m/s Speed 3, 4.5 m/s Speed 2, 3.5 m/s Speed 1, 2.5 m/s	Speed 32, ≥6.5 m/s Speed 30, ≥6.0 m/s Speed 20, ≥4.5 m/s Speed 10 , ≥3.0 m/s Speed 1 , ≥1.0 m/s

FEATURES

C8

90°
UP & DOWN

360°
LEFT & RIGHT

360° OSCILLATION
AUTO ROTATION

AC MOTOR

50W

3 WIND MODES*
WITH 5 SPEED
SETTINGS

*NORMAL/ NATURE/
SLEEPING MODE

0800

HOURS MINUTES

TIMER

1-8 HRS TIMING

RM 0.24

PER DAY

C8 DC

90°
UP & DOWN

360°
LEFT & RIGHT

360° OSCILLATION
AUTO ROTATION

DC MOTOR

26W

3 WIND MODES*
WITH 32 SPEED
SETTINGS

*NORMAL/ NATURE/
SLEEPING MODE

1200

HOURS MINUTES

TIMER

1-12 HRS TIMING

RM 0.12

PER DAY

*COST ARE CALCULATED WITH THE TNB APPLIANCE CALCULATOR FOR 12 HOURS FRAME